



Full-Height CS Overtaking Doors cavity slider with AluTec door leaves



Cavity Slider with AluTec door



AutoCav with AluTec door



Full-Height track with AluTec



Features

The **CS AluTec™** is a top of the line flush aluminium door leaf suitable for a wide range of applications, including sliding and hinged. It is designed to withstand the elements and may be used in both interior and exterior situations.

- ▮ The frame is constructed entirely of aluminium to reduce the risk of bowing.
- ▮ Stable construction makes the AluTec ideal for oversized doors.
- ▮ Hidden fixings are made from either zinc coated steel or aluminium.
- ▮ Easy to clean and maintain.
- ▮ Doors are supplied pre-primed, ready for final paint.
- ▮ Available in door sizes up to 3m high x 4.5m wide (large doors may require a vertical sheet join).
- ▮ CaviLock and other hinged door hardware can be factory fitted, ensuring a perfect fit every time.

Technical Information

- 1 The top rail has been designed to take the CS quick release mounting plates for sliding doors.
- 2 Once installed, there are no visible screws or fastenings.
- 3 A 'U' guide is fitted for sliding doors, ensuring a perfect slide every time.
- 4 A neat edge clashing detail runs down the two vertical edges of the door.



How to specify (example)

Product:	~	CS AluTec DoorLeaves
Location:	~	Boardroom
Leaf dimensions:	~	2700mm x 1200mm
Finish/colour:	~	Matt Titania
Application:	~	Cavity slider
Hardware:	~	CL400® Magnetic Key/Snib

Full specifications: www.natspec.com.au

Quality

CS manufactured door leaves come with a **five year warranty**, making the CS AluTec a suitable alternative to timber doors when a door over 1020mm wide is required.

Options

The CS AluTec is supplied pre-primed. Arrives ready for top coat finishing on site by a trade qualified painter.

AluTec® SoundStop®

Our specialised **AluTec SoundStop** aluminium door leaf can be used with the SoundStop cavity slider.

It has been tested to STC 36/RW 36 dB and is suitable for single doors up to 2500 x 2200mm. GIB® Noiseline® 13mm linings must be used with this option.



Applications



Cavity Slider



Surface Slider



Pre-Hung (Hinged)

Sliding Door Hardware



CL100 Flush Turn



CL400 Magnetic



Aluminium Edge Pull & Louey



CL100 Louise



Oversized 'D' Pull



CL200