

# AutoCav® Selection Chart

Features	Residential	Commercial
90mm framing	✓	✓
140mm framing	✓	✓
Maximum door size	2400 H x 1100mm W	3000 H x 4500mm W
Maximum door weight - Single	100kg	200kg
Maximum door weight - Bi-Parting	60kg	130kg
Low security lock	Optional extra	
High security lock		✓
Fire inputs		✓
Opening speed	400 - 500 mm/sec	20 - 600 mm/sec
Closing speed	100 - 500 mm/sec	20 - 600 mm/sec
Variable speed control		✓
Force to open	✓	✓
Hold open configurable		✓
Partial open		✓
Fault monitoring		✓
Online commissioning		✓
4 inputs (2x activation, 2x lock)	✓	
6 inputs		✓
Home automation integration	✓	✓
UPS/Battery backup		✓
Safety Beams	Optional extra	✓
<b>Activation</b>		
PDL switch	✓	✓
Overhead sensor	Optional extra	✓
Handwave sensor	Optional extra	✓
Multiple activation switches		✓
Configurable multi function button		✓
Secure mode programmable		✓
PLC - Customer supplied activation	✓	✓



**CS FOR DOORS NZ**  
0800 754 337



[www.csfordoors.co.nz](http://www.csfordoors.co.nz)  
info@csfordoors.co.nz



[www.cavitysliders.com.au](http://www.cavitysliders.com.au)  
info@cavitysliders.com.au



**CS Cavity Sliders AU**  
1800 975 433